

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: C5101, C5100
Product name: MAX - TRASPARENTE ACRILICO H.S.,
MAX - TRASPARENTE ACRILICO M.S.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: acrylic Clearcoat. Professional use only.

Uses advised against: no one in particular

1.3. Details of the supplier of the safety data sheet

Name: ILPA ADESIVI SRL
Full address: Via Ferorelli, 4
District and Country: 70132 BARI (BARI)
ITALIA
Tel. + 39 0805383837
Fax + 39 0805377807

e-mail address of the competent person

responsible for the Safety Data Sheet: aborricelli@ilpa.it

1.4. Emergency telephone number

For urgent inquiries refer to: + 39 3355405598 (Technical support - 8,00 - 17,00 - LUN-VEN; MON-FRI)(Italian time zone)
Safety Executive (HSE) Chemicals Regulation Directorate 5S.1 Redgrave Court, Merton Road, Bootle, Merseyside. L20 7HS.
Phone: +44 151 9513317

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains: 2-hydroxyethyl methacrylate , bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate , REACTION MASS OF A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-HYDROXYPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE).
	May produce an allergic reaction.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves / eye protection / face protection.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P370+P378	In case of fire: use carbon dioxide, foam, chemical powder to extinguish.

Contains:	XYLENE (MIXTURE OF ISOMERS) N-BUTYL ACETATE HYDROCARBONS, C9, AROMATICS ETHYL ACETATE
------------------	--

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

C5101 – MAX - TRASPARENTE ACRILICO

3.2. Mixtures.

Contains:

Identification.

Conc. %.

Classification 1272/2008 (CLP).

N-BUTYL ACETATE

CAS. 123-86-4

21 - 22,5

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC. 204-658-1

INDEX. 607-025-00-1

Reg. no. 01-2119485493-29

XYLENE (MIXTURE OF ISOMERS)

CAS. 1330-20-7

10 - 11,5

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Note C

EC. 215-535-7

INDEX. 601-022-00-9

Reg. no. 01-2119488216-32

HYDROCARBONS, C9, AROMATICS

CAS. -

8 - 9

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066

EC. 918-668-5

INDEX. -

Reg. no. 01-2119455851-35

ETHYL ACETATE

CAS. 141-78-6

2 - 2,5

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC. 205-500-4

INDEX. 607-022-00-5

Reg. no. 01-2119475103-46

2-METHOXY-1-METHYLETHYL ACETATE

CAS. 108-65-6

1 - 1,5

Flam. Liq. 3 H226

EC. 203-603-9

INDEX. 607-195-00-7

Reg. no. 01-2119475791-29

ETHYLBENZENE

CAS. 100-41-4

0,5 - 0,6

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

EC. 202-849-4

INDEX. 601-023-00-4

Reg. no. 01-2119489370-35

REACTION MASS OF A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-HYDROXYPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE).

CAS. -

0,5 - 0,6

Skin Sens. 1 H317, Aquatic

Chronic 2 H411

EC. 400-830-7

INDEX. 607-176-00-3

Reg. no. 01-2119396032-43-0000

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

CAS. 41556-26-7

0,2 - 0,25

Skin Sens. 1 H317, Aquatic
Acute 1 H400 M=1, Aquatic
Chronic 1 H410

EC. 255-437-1

INDEX. -

2-hydroxyethyl methacrylate

CAS. 868-77-9

0,1 - 0,15

Eye Irrit. 2 H319, Skin Irrit. 2
H315, Skin Sens. 1 H317,
Note D

EC. 212-782-2

INDEX. 607-124-00-X

Reg. no. 01-2119490169-29

2-BUTOXYETHANOL

CAS. 111-76-2

0 - 0,05

Acute Tox. 4 H302, Acute
Tox. 4 H312, Acute Tox. 4
H332, Eye Irrit. 2 H319, Skin
Irrit. 2 H315

EC. 203-905-0

INDEX. 603-014-00-0

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

PROTECTIVE MEASURES FOR THE FIRST RESCUE WORKERS: for PPE (personal protection equipment) required for first aid refer to section 8.2 of this safety data sheet.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for safe handling.**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

No use other than specified in Section 1.2 of this safety data sheet.

SECTION 8. Exposure controls/personal protection.**8.1. Control parameters.**

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail 2012. / Grenzwerte am Arbeitsplatz
CYP	Κύπρος	Κ.Δ.Π. 268/2001; Κ.Δ.Π. 55/2004; Κ.Δ.Π. 295/2007; Κ.Δ.Π. 70/2012
CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
EST	Eesti	Töökeskkonna keemiliste ohutegurite piirnormid 1. Vastu võetud 18.09.2001 nr 293 RT I 2001, 77, 460 - Redaktsiooni jõustumise kp: 01.01.2008
FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveystieteiden ministeriön julkaisu 2012:5
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9

HRV	Hrvatska	Φεβρουαρίου 2012
HUN	Magyarország	NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva
IRL	Éire	50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról
ITA	Italia	Code of Practice Chemical Agent Regulations 2011
LTU	Lietuva	Decreto Legislativo 9 Aprile 2008, n.81
LVA	Latvija	DĒL LIETUVOS HIGIENOS NORMOS HN 23:2007 CHEMINIŲ
NLD	Nederland	MEDŽIAGŲ 2007 m. spalio 15 d. Nr. V-827/A1-287
NOR	Norge	Κίμικο vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā
POL	Polska	2012
SVK	Slovensko	Databank of the social and Economic Concil of Netherlands (SER) Values,
SVN	Slovenija	AF 2011:18
SWE	Sverige	Veiledning om Administrative normer for forurensning i arbeidsatmosfære
TUR	Türkiye	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia
EU	OEL EU	16 grudnia 2011r
	TLV-ACGIH	NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007
		Uradni list Republike Slovenije 15. 6. 2007
		Occupational Exposure Limit Values, AF 2011:18
		2000/39/EC sayılı Direktifin ekidir
		Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;
		Directive 2000/39/EC.
		ACGIH 2014

N-BUTYL ACETATE
Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	AUS	480	100	480	100
VLEP	BEL	723	150	964	200
TLV	BGR	710		950	
VEL	CHE	480	100	960	200
MAK	CHE	480	100	960	200
TLV	CZE	950		1200	
MAK	DEU	480	100	960	200
VLA	ESP	724	150	965	200
VLEP	FRA	710	150	940	200
WEL	GBR	724	150	966	200
TLV	GRC	710	150	950	200
GVI	HRV	724	150	966	200
AK	HUN	950		950	
OEL	IRL	710	150	950	200
OEL	NLD	150			
TLV	NOR		75		
NDS	POL	200		950	
NPHV	SVK	480	100	960	
MAK	SWE	500	100	700	150
TLV-ACGIH		713	150	950	200

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg/d
Normal value for marine water sediment	0,0981	mg/kg/d

ILPA ADESIVI SRL						Revision nr. 1		
C5101 – MAX - TRASPARENTE ACRILICO						Dated 13/05/2016		
						Printed on 16/05/2016		
						Page n. 8/26		
Normal value for water, intermittent release						0,36	mg/l	
Normal value of STP microorganisms						35,6	mg/l	
Normal value for the terrestrial compartment						0,0903	mg/kg/d	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation.	859,7 mg/m3	859,7 mg/m3	102,34 mg/m3	102,34 mg/m3	960 mg/m3	960 mg/m3	480 mg/m3	480 mg/m3
XYLENE (MIXTURE OF ISOMERS)								
Threshold Limit Value.								
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
MAK	AUS	221	50	442	100	SKIN.		
VLEP	BEL	221	50	442	100	SKIN.		
TLV	BGR	221		442		SKIN.		
TLV	CYP	221	50	442	100	SKIN.		
TLV	CZE	200		400		SKIN.		
AGW	DEU	440	100	880	200	SKIN.		
MAK	DEU	440	100	880	200	SKIN.		
VLA	ESP	221	50	442	100	SKIN.		
TLV	EST	221	50	442	100	SKIN.		
HTP	FIN	220	50	440	100	SKIN.		
VLEP	FRA	221	50	442	100	SKIN.		
WEL	GBR	220	50	441	100			
TLV	GRC	435	100	650	150			
GVI	HRV	221	50	442	100	SKIN.		
AK	HUN	221		442		SKIN.		
OEL	IRL	221	50	442	100	SKIN.		
TLV	ITA	221	50	442	100	SKIN.		
OEL	NLD	210		442		SKIN.		
TLV	NOR	108	25			SKIN.		
NDS	POL	100						
NPHV	SVK	221	50	442		SKIN.		
MV	SVN	221	50			SKIN.		
MAK	SWE	221	50	442	100	SKIN.		
ESD	TUR	221	50	442	100	SKIN.		
OEL	EU	221	50	442	100	SKIN.		
TLV-ACGIH		434	100	651	150			
Predicted no-effect concentration - PNEC.								
Normal value in fresh water						0,327	mg/l	
Normal value in marine water						0,327	mg/l	
Normal value for fresh water sediment						12,46	mg/kg/d	
Normal value for marine water sediment						12,46	mg/kg/d	
Normal value for water, intermittent release						0,327	mg/l	
Normal value of STP microorganisms						6,58	mg/l	
Normal value for the terrestrial compartment						2,31	mg/kg/d	
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	1,6 mg/kg bw/d				

ILPA ADESIVI SRL						Revision nr. 1		
						Dated 13/05/2016		
C5101 – MAX - TRASPARENTE ACRILICO						Printed on 16/05/2016		
						Page n. 9/26		
Inhalation. Skin.	174 mg/m3	174 mg/m3	VND VND	14,8 mg/m3 108 mg/kg bw/d	289 mg/m3	289 mg/m3	VND VND	77 mg/m3 180 mg/kg bw/d
HYDROCARBONS, C9, AROMATICS								
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	11 mg/kg bw/d				
Inhalation.			VND	32 mg/m3			VND	150 mg/m3
Skin.			VND	11 mg/kg bw/d			VND	25 mg/kg bw/d
ETHYL ACETATE								
Threshold Limit Value.								
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
MAK	AUS	1050	300	2100	600			
VLEP	BEL	1461	400					
TLV	BGR	800						
VEL	CHE	1400	400	2800	800			
MAK	CHE	1400	400	2800	800			
TLV	CZE	700		900				
AGW	DEU	1500	400	3000	800			
MAK	DEU	1500	400	3000	800			
TLV	DNK	540	150					
VLA	ESP	1460	400					
TLV	EST	500	150	1100	300			
HTP	FIN	1100	300	1800	500			
VLEP	FRA	1400	400					
WEL	GBR		200		400			
TLV	GRC	1400	400					
GVI	HRV		200		400			
AK	HUN	1400		1400				
OEL	IRL		200		400			
RD	LTU	500	150	1100 (C)	300 (C)			
RV	LVA	200						
OEL	NLD	550		1100				
TLV	NOR	550	150					
NDS	POL	200		600				
NPHV	SVK	1500	400	3000				
MAK	SWE	500	150	1100	300			
TLV-ACGIH		1441	400					
Predicted no-effect concentration - PNEC.								
Normal value in fresh water				0,24		mg/l		
Normal value in marine water				0,024		mg/l		
Normal value for fresh water sediment				1,15		mg/kg/d		
Normal value for marine water sediment				0,115		mg/kg/d		
Normal value for water, intermittent release				1,65		mg/l		
Normal value of STP microorganisms				650		mg/l		
Normal value for the food chain (secondary poisoning)				200		mg/kg		
Normal value for the terrestrial compartment				0,148		mg/kg/d		

C5101 – MAX - TRASPARENTE ACRILICO

Normal value for the atmosphere

NPI

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic 4,5 mg/kg bw/d	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND					
Inhalation.	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin.			VND	37 mg/kg bw/d			VND	63 mg/kg bw/d

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	
MAK	AUS	275	50	550	100	SKIN.
VLEP	BEL	275	50	550	100	SKIN.
TLV	BGR	275		550		SKIN.
TLV	CYP	275	50	550	100	SKIN.
TLV	CZE	270		550		SKIN.
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	DNK	275	50			SKIN.
VLA	ESP	275	50	550	100	SKIN.
HTP	FIN	270	50	550	100	SKIN.
VLEP	FRA	275	50	550	100	SKIN.
WEL	GBR	274	50	548	100	
TLV	GRC	275	50	550	100	
AK	HUN	275		550		
OEL	IRL	275	50	550	100	SKIN.
TLV	ITA	275	50	550	100	SKIN.
RD	LTU	250	50	400	75	SKIN.
RV	LVA	275	50	550	100	SKIN.
OEL	NLD	550				
TLV	NOR	270	50			SKIN.
NDS	POL	260		520		
NPHV	SVK	275	50	550		SKIN.
MAK	SWE	250	50	400	75	SKIN.
ESD	TUR	275	50	550	100	SKIN.
OEL	EU	275	50	550	100	SKIN.

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic 1,67 mg/kg bw/d	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND					

[illegible]

C5101 – MAX - TRASPARENTE ACRILICO

REACTION MASS OF A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-HYDROXYPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE).

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,023	mg/l
Normal value in marine water	0,00046	mg/l
Normal value for fresh water sediment	0,726	mg/kg/d
Normal value for marine water sediment	0,726	mg/kg/d
Normal value for water, intermittent release	0,023	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	14,52	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	0,025 mg/kg bw/d				
Inhalation.			VND	0,099 mg/m3	NPI	NPI	NPI	0,398 mg/m3
Skin.			VND	0,025 mg/kg bw/d			VND	0,25 mg/kg bw/d

2-hydroxyethyl methacrylate

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,482	mg/l
Normal value for fresh water sediment	3,79	mg/kg/d
Normal value for marine water sediment	3,79	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			NPI	0,83 mg/kg bw/d				
Inhalation.	NPI	NPI	NPI	2,9 mg/m3	NPI	NPI	NPI	4,9 mg/m3
Skin.	NPI	NPI	NPI	0,83 mg/kg bw/d	NPI	NPI	NPI	1,3 mg/kg bw/d

DIBUTYLTIN DILAURATE

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,000463	mg/l
Normal value in marine water	0,000463	mg/l
Normal value for fresh water sediment	0,05	mg/kg
Normal value for marine water sediment	0,005	mg/kg
Normal value for water, intermittent release	0,00463	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,0407	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	0,02 mg/kg bw/d	VND	0,004 mg/kg bw/d				
Inhalation.	NPI	0,04 mg/m3	NPI	0,006 mg/m3	NPI	NPI	NPI	0,02 mg/m3
Skin.	NPI	1 mg/kg bw/d	NPI	0,16 mg/kg bw/d	VND	2,08 mg/kg bw/d	VND	0,42 mg/kg bw/d

2-BUTOXYETHANOL

Threshold Limit Value.

Type	Country	TWA/8h	ppm	STEL/15min	ppm
		mg/m3	ppm	mg/m3	ppm

C5101 – MAX - TRASPARENTE ACRILICO

MAK	AUS	98	20	200	40	SKIN.
VLEP	BEL	98	20	246	50	SKIN.
TLV	BGR	98		246		SKIN.
VEL	CHE	49	10	98	20	SKIN.
MAK	CHE	49	10	98	20	SKIN.
TLV	CYP	98	20	246	50	SKIN.
TLV	CZE	100		200		SKIN.
AGW	DEU	49	10	196	40	SKIN.
MAK	DEU	49	10	98	20	SKIN.
TLV	DNK	98	20			SKIN.
VLA	ESP	98	20	245	50	SKIN.
TLV	EST	98	20	246	50	SKIN.
HTP	FIN	98	20	246	50	SKIN.
VLEP	FRA	49	10	246	50	SKIN.
WEL	GBR	123	25	246	50	SKIN.
TLV	GRC	120	25			
GVI	HRV	98	20	246	50	SKIN.
AK	HUN	98		246		
OEL	IRL	98	20	246	50	SKIN.
TLV	ITA	98	20	246	50	SKIN.
RD	LTU	50	10	100	20	SKIN.
RV	LVA	98	20	246	50	SKIN.
OEL	NLD	100		246		SKIN.
TLV	NOR	50	10			SKIN.
NDS	POL	98		200		
NPHV	SVK	98	20	246		SKIN.
MV	SVN	98	20			SKIN.
MAK	SWE	50	10	100	20	SKIN.
ESD	TUR	98	20	246	50	SKIN.
OEL	EU	98	20	246	50	SKIN.
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC.

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l
Normal value for fresh water sediment	34,6	mg/kg/d
Normal value for marine water sediment	3,46	mg/kg/d
Normal value for water, intermittent release	9,1	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the terrestrial compartment	2,33	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	26,7 mg/kg bw/d	VND	6,3 mg/kg bw/d				
Inhalation.	147 mg/m3	426 mg/m3	NPI	59 mg/m3	246 mg/m3	1091 mg/m3	NPI	98 mg/m3
Skin.	VND	89 mg/kg bw/d	NPI	75 mg/kg bw/d	NPI	89 mg/kg bw/d	NPI	125 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

XYLENI: Biological Exposure Indices (IBE): Hippuric Acid in urine: 1.5 g/g creatinina. Sampling time: End of shift. (ACGIH 2014).

ETHYLBENZENE: Biological Exposure Indices (IBE): mandelic acid + phenylglyoxylic acid in urine: 0,7 g/g creatinine. Sampling time: End of shift (ACGIH 2014)
ethylbenzene end-expiratory air: not critical (ACGIH 2014).

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	colourless
Odour	aromatic
Odour threshold.	0,47 ppm (p-XYLENE).
pH.	0,5 – 1,0 ppm (XYLENE: MIXTURE OF ISOMERS).
Melting point / freezing point.	Not applicable.
	13,2°C (p-XYLENE)
	-49,9°C (m-XYLENE)
	-25,2 °C (o-XYLENE)
Initial boiling point.	> 35 °C.
Boiling range.	77°C (ETHYL ACETATE, ICSC 0367).
	135 – 145 °C (PUBCHEM CID: 6850715) (XYLENE: MIXTURE OF ISOMERS).
Flash point.	< 23 °C.
Evaporation rate	0,75 (butyl acetate = 1) (XYLENE: MIXTURE OF ISOMERS)
Flammability (solid, gas)	not applicable
	1,1 Vol% (p-XYLENE)
	1,1 Vol% (m-XYLENE)
	0,9 Vol% (o-XYLENE)
Upper inflammability limit.	7 Vol% (p-XYLENE)
	7 Vol% (m-XYLENE)
	6,7 Vol% (o-XYLENE)
Lower explosive limit.	1,1 (in air Vol%) (ICSC 0086) (p-XYLENE)
	1,1 (in air Vol%) (ICSC 0085) (m-XYLENE)
	0,9 (in air Vol%) (ICSC 0084) (o-XYLENE)
Upper explosive limit.	7 (in air Vol%) (ICSC 0086) (p-XYLENE)
	7 (in air Vol%) (ICSC 0085) (m-XYLENE)
	6,7 (in air Vol%) (ICSC 0084) (o-XYLENE)
Vapour pressure.	0,186 PSI (T=26,6°C) (p-XYLENE)
	0,207 PSI (T=29,4°C) (m-XYLENE)
	0,194 PSI (T=32,2°C) (o-XYLENE)
Vapour density	3,7 (air=1) (T=20°C) (ICSC 0086) (p-XYLENE)
	3,7 (air=1) (T=20°C) (ICSC 0085) (m-XYLENE)
	3,7 (air=1) (T=20°C) (ICSC 0084) (o-XYLENE)
Relative density.	0,980 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	3,15 log Pow (T=20°C) (p-XYLENE)
	3,2 log Pow (T=20°C) (m-XYLENE)
	3,12 log Pow (T=20°C) (o-XYLENE)
Auto-ignition temperature.	528°C (1 Bar) (p-XYLENE)
	527°C (1 Bar) (m-XYLENE)
	463°C (1 Bar) (o-XYLENE)
Decomposition temperature.	not applicable
Viscosity	100 cPs (T = 20 °C)
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information.

VOC (Directive 2004/42/EC) :	43,94 % - 430,62 g/litre.
VOC (volatile carbon) :	Not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL ACETATE: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.

2-BUTOXYETHANOL: decomposes in the presence of heat.

ETHYL ACETATE: decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

N-BUTYL ACETATE: decomposes readily with water, especially when warm.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

1-METHOXY-2-PROPANOL ACETATE: may react violently with oxidising agents and strong acids and alkaline metals.

ETHYLBENZENE: reacts violently with strong oxidising agents and attacks various types of plastics. Can form explosive mixtures with the air.

2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

ETHYL ACETATE: risk of explosion on contact with: metals, alkalis, hydrides. oleum. can react violently with: fluoride, strong oxidising agents, chlorosulfuric acid, potassium tert-butoxide. Forms explosive mixtures with the air.

N-BUTYL ACETATE: risk of explosion on contact with: strong oxidising agents. Can react dangerously with alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL ACETATE: store in an inert atmosphere, sheletered from moisture because it hydrolises easily.

2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

ETHYL ACETATE: avoid exposure to light, sources of heat and naked flames.

N-BUTYL ACETATE: avoid exposure to moisture, sources of heat and naked flames.

10.5. Incompatible materials.

1-METHOXY-2-PROPANOL ACETATE: oxidising agents, strong acids and alkaline metals.

ETHYL ACETATE: acids and bases, strong oxidising agents; aluminium and some plastics, nitrates and chlorosulphuric acid.

N-BUTYL ACETATE: water, nitrates, strong oxidising agents, acids and alkalis and potassium tert-butoxide.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE: methane, styrene, hydrogen, ethane.

2-BUTOXYETHANOL: hydrogen.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human

body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product contains sensitizing substance/s and may cause allergic reactions.

11.1. Information on toxicological effects.

Data refers to the mix:

ACUTE TOXICITY: No data available

SKIN CORROSION/IRRITATION: Causes skin irritation (section 3.2 of the safety data sheet)

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye irritation (section 3.2 of the safety data sheet)

RESPIRATORY OR SKIN SENSITISATION: Contains (section 2.2 of the safety data sheet). May produce an allergic reaction (section 3.2 of the safety data sheet)

GERM CELL MUTAGENICITY: No data available

CARCINOGENICITY: No data available

REPRODUCTIVE TOXICITY: No data available

STOT-SINGLE EXPOSURE: May cause drowsiness or dizziness. (section 3.2 of the safety data sheet)

STOT-REPEATED EXPOSURE: Causes damage to organs through prolonged or repeated exposure (section 3.2 of the safety data sheet)

ASPIRATION HAZARD: not relevant to viscosity values (section 9 of the safety data sheet)

Data relating to substances hazardous mixture:

2-HYDROXYETHYL METHACRYLATE

ACUTE TOXICITY:

LD50 (Oral).5564 mg/kg RAT, according to (FDA, 1959 in food, drugs and cosmetics)

LD50 (Dermal).> 5000 mg/kg RABBIT, (standard acute method)

SERIOUS EYE DAMAGE/IRRITATION: Causes eyes irritation, Rabbit (Appraisal of the safety of Chemicals in foods, drugs and cosmetics by staff of the Division of Pharmacology, FDA acc. to Draize);

RESPIRATORY OR SKIN SENSITISATION: Causes skin irritation. species: guinea pig maximisation test (Magnusson and Kligman (1970)).

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

ACUTE TOXICITY:

LD50 (Oral).3523 mg/kg Rat (equivalent or similar to EU Method B.1)

LD50 (Dermal).4200 mg/kg Rabbit (Industrial Medicine 39, 215-200, 1970)

LC50 (Inhalation).26 mg/l/4h Rat(equivalent or similar to EU Method B.2)

SKIN CORROSION/IRRITATION: Causes skin irritation. (test in vivo, Rabbit, Industrial Medicine 39, 215-200.)

SERIOUS EYE DAMAGE/IRRITATION: Causes eyes irritation (Draize Test, Rabbit, exposure time 24h)

RESPIRATORY OR SKIN SENSITISATION: not sensitizing. (mouse, OECD Guideline 429)

GERM CELL MUTAGENICITY: negative, (Mouse, test in vivo, Equivalent or similar to OECD Guideline 478)

CARCINOGENICITY: negative, (mouse, Equivalent or similar to EU Method B.32)

REPRODUCTIVE TOXICITY: NOEC = 100 ppm (parental systemic toxicity), NOAEC >500 ppm (reproductive and developmental toxicity) (Rat, Equivalent or similar to EPA OPPTS 870.3800)

STOT-SINGLE EXPOSURE: May cause respiratory irritation. (Environmental Toxicology and Pharmacology, Vol 14, pp 129-137)

STOT-REPEATED EXPOSURE: Causes damage to organs: central nervous system, liver and kidneys, through prolonged or repeated exposure, (Rat, Metodo OECD Guideline 408).

ASPIRATION HAZARD: May be fatal if swallowed and enters airways. (Annex VI, REGULATION (EC) No 1272/2008).

1-METHOXY-2-PROPANOL ACETATE: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

ACUTE TOXICITY:

LD50 (Oral).8530 mg/kg Rat

LD50 (Dermal).> 5000 mg/kg Rat

ETHYLBENZENE: like the benzene homologues, may exert an effect on the CNS with depression, narcosis, often preceded by dizziness and accompanied by headache. It is irritating to the skin, conjunctivae and respiratory apparatus.

ACUTE TOXICITY:

LD50 (Oral).3500 mg/kg Rat (standard acute method)

LD50 (Dermal).15354 mg/kg Rabbit (standard acute method)

C5101 – MAX - TRASPARENTE ACRILICO

LC50 (Inhalation).17,8 mg/l/4h Rat (standard acute method)

ETHYL ACETATE**ACUTE TOXICITY:**

LD50 (Oral).4934 mg/kg Rabbit (Equivalent to OECD 401)

LD50 (Dermal).20000 mg/kg Rabbit (Publication Am Ind Hyg Ass J, 23, 95)

LC50 (Inhalation).22,5 mg/l/6h Rat (40 CFR Part 799 (58 FR 40262))

SKIN CORROSION/IRRITATION: Skin slightly irritating (Rabbit, OECD 404)

SERIOUS EYE DAMAGE/IRRITATION: irritating to eyes (Annex VI, REGULATION (EC) No 1272/2008).

RESPIRATORY OR SKIN SENSITISATION: not sensitizing (Guinea pig, OECD Guideline 406)

GERM CELL MUTAGENICITY: negative, (Hamster, Equivalent or similar to OECD Guideline 474)

CARCINOGENICITY: No data available.

REPRODUCTIVE TOXICITY: NOAEL = 26400 mg/kg (Mouse, Read-across from supporting substance, equivalent or similar to OECD Guideline 416)

STOT-SINGLE EXPOSURE: It can cause respiratory irritation (Annex VI, REGULATION (EC) No 1272/2008).

STOT-REPEATED EXPOSURE:

Orale: NOAEL = 900 mg/kg bw/day (Rat, Equivalent or similar to EPA OTS 795.2600, GLP)

Inalation: NOAEL = 350 ppm (Rat, EPA OTS 798.2450, GLP)

ASPIRATION HAZARD: May be fatal if swallowed and enters airways. (Annex VI, REGULATION (EC) No 1272/2008).

N-BUTYL ACETATE:in humans the substance's vapours cause irritation to the eues and nose. In the event of repeated exposure, there is skin irritation, dermatosis (with driness and flaking of the skin) and keratitis.

ACUTE TOXICITY:

LD50 (Oral).10760 mg/kg Rat (Equivalent or similar to OECD Guideline 423)

LD50 (Dermal).14112 mg/kg Rabbit (Equivalent or similar to OECD Guideline 402)

LC50 (Inhalation).5,3 mg/l/4h Rat (Equivalent or similar to OECD Guideline 423)

SKIN CORROSION/IRRITATION: non-irritating (Rabbit, Equivalent or similar to OECD Guideline 404)

SERIOUS EYE DAMAGE/IRRITATION: non-irritating (Rabbit, OECD Guideline 405)

RESPIRATORY OR SKIN SENSITISATION: No data available

GERM CELL MUTAGENICITY: negative, test in vivo (Read-across from supporting substance, OECD Guideline 474, GLP)

CARCINOGENICITY: No data available

REPRODUCTIVE TOXICITY: no teratogenic effect. NOEC (fertilità) = 2000 ppm, NOAEC (developmental toxicity) = 750 ppm, NOAEC (systemic toxicity) = 750 ppm. (Rat, OECD Guideline 416, GLP)

STOT-SINGLE EXPOSURE: May cause drowsiness or dizziness. (Annex VI, REGULATION (EC) No 1272/2008)

STOT-REPEATED EXPOSURE: NOAEC = 500 ppm (Rat, EPA OTS 798.2450)

ASPIRATION HAZARD: No data available.

HYDROCARBONS, C9, AROMATICS**ACUTE TOXICITY:**

LD50 (Oral).3492 mg/kg Rat (Study report ECHA)

LD50 (Dermal).3160 mg/kg Rabbit (Equivalent or similar to OECD Guideline 402)

LC50 (Inhalation).6193 ppm/4h Rat (Equivalent or similar to OECD Guideline 403, GLP)

SKIN CORROSION/IRRITATION: Causes skin irritation. (Ref. SDS supplier)

SERIOUS EYE DAMAGE/IRRITATION: Causes eye irritation. (Ref. SDS supplier)

STOT-SINGLE EXPOSURE: May cause respiratory irritation and ay cause drowsiness or dizziness. (Ref. SDS supplier)

ASPIRATION HAZARD: May be fatal if swallowed and enters airways. (Ref. SDS supplier).

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE**ACUTE TOXICITY:**

LD50 = 3200 mg/kg, CAVIA (SDS fornitore).

2-BUTOXYETHANOL**ACUTE TOXICITY:**

LD50 (Oral).615 mg/kg Rat

LD50 (Dermal).405 mg/kg Rabbit

LC50 (Inhalation).2,2 mg/l/4h Rat

REACTION MASS OF A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-HYDROXYPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE).**ACUTE TOXICITY:**

LD50 (Oral).> 5000 mg/kg Rat, according to (OECD Guideline No. 401)

LD50 (Dermal).> 2000 mg/kg rat, according to (OECD Guideline No. 402)

LC50 (Inhalation).> 5,8 mg/l/4h rat, according to (OECD 403). (Fully conforms with Annex V, B2)

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
EC50 = 20 ppm/24h, Daphnia magna (by SDS supplier)
LC50 = 1,0 ppm/96h, Iepomis macrochirus (by SDS supplier).

2-hydroxyethyl methacrylate

LC50 - for Fish. > 100 mg/l/96h Oryzias latipes, according to (OECD Guideline 203)
EC50 - for Crustacea. 380 mg/l/48h Daphnia magna, according to (OECD Guideline 202)
EC50 - for Algae / Aquatic Plants. 345 mg/l/72h Selenastrum capricornutum, according to (OECD Guideline 201)
Chronic NOEC for Crustacea. 24,1 mg/l 21 d Daphnia magna (OECD Guideline 211 (Daphnia magna Reproduction Test))

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish. 2,6 mg/l/96h Oncorhynchus mykiss (OECD TG 203)
Chronic NOEC for Fish. 1,3 mg/l 56d Oncorhynchus mykiss (Appl. Sci. Branch, Eng. Res. Cent. Denver, CO: 15p.)
Chronic NOEC for Crustacea. 1,17 mg/l 7d Ceriodaphnia dubia (Ecotoxicology and Environmental Safety 39, 136-146)

2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish. 134 mg/l/96h Oncorhynchus mykiss (OECD Guideline 203)
EC50 - for Crustacea. 500 mg/l/48h Daphnia magna (EU Method C.2)

ETHYLBENZENE

LC50 - for Fish. 4,2 mg/l/96h Oncorhynchus mykiss, according to (OECD Guideline 203)
EC50 - for Crustacea. 2,4 mg/l/48h Daphnia magna, According to EPA method F
EC50 - for Algae / Aquatic Plants. 5,4 mg/l/72h Selenastrum capricornutum, according to (U.S. EPA.1985 Federal register, Volume 50, Number 188)

2-BUTOXYETHANOL

LC50 - for Fish. 1474 mg/l/96h Oncorhynchus mykiss, according to (OECD Guideline 203)
EC50 - for Crustacea. 1550 mg/l/48h Daphnia magna, according to (OECD Guideline 202)
EC50 - for Algae / Aquatic Plants. 911 mg/l/72h Pseudokirchnerella subcapitata, according to (OECD Guideline 201)

ETHYL ACETATE

LC50 - for Fish. 230 mg/l/96h Pimephales promelas (US EPA method E03-05)
EC50 - for Crustacea. 165 mg/l/48h Daphnia (Rif. SDS fornitore)
Chronic NOEC for Crustacea. 100 mg/l Scenedesmus subspicatus (OECD Guideline 201, GLP)

N-BUTYL ACETATE

LC50 - for Fish. 18 mg/l/96h Pimephales promelas (Equivalent or similar to OECD Guideline 203)
EC50 - for Crustacea. 44 mg/l/48h Daphnia sp. (Publication, 1959, no guideline followed)
EC50 - for Algae / Aquatic Plants. 648 mg/l/72h Desmodesmus subspicatus (Umweltbundesamt - German Federal Environment Agency)
Chronic NOEC for Crustacea. 23 mg/l Daphnia magna, 21 d (Read-across from supporting substance, OECD Guideline 211)

HYDROCARBONS, C9, AROMATICS

C5101 – MAX - TRASPARENTE ACRILICO

LC50 - for Fish.	9,2 mg/l/96h Oncorhynchus mykiss (OECD Guideline 203, GLP)
EC50 - for Crustacea.	3,2 mg/l/48h Daphnia magna (OECD Guideline 202, GLP)
EC50 - for Algae / Aquatic Plants.	2,6 mg/l/72h Raphidocelis subcapitata (OECD Guideline 201, GLP)

REACTION	MASS	OF	A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL- Ω -HYDROXPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL- Ω -3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXPOLY(OXYETHYLENE).
LC50 - for Fish.	2,8 mg/l/96h	Oncorhynchus mykiss,	according to (OECD Guideline 203)
EC50 - for Crustacea.	4 mg/l/48h	daphnia magna,	according to (EPA Guideline EG-1)
EC50 - for Algae / Aquatic Plants.	9 mg/l/72h	Selenastrum capricornutum,	according to (OECD Guideline 201)

12.2. Persistence and degradability.

N-BUTYL ACETATE
Readily biodegradable: 83% in 28 days (Metod OECD TG 301 D).

2-hydroxyethyl methacrylate
Rapidly biodegradable.

92-100% after 14 days, according to (OECD Guideline 301 C)

XYLENE (MIXTURE OF ISOMERS)
Solubility in water. mg/l 100 - 1000 Handbook of aqueous solubility data.
Rapidly biodegradable.

OECD Guideline 301 F, GLP

2-METHOXY-1-METHYLETHYL ACETATE
Solubility in water. > 10000 mg/l
Rapidly biodegradable.

(OECD Guideline 301 F, GLP)

ETHYLBENZENE
Solubility in water. mg/l 1000 - 10000
Rapidly biodegradable.

ISO 14593-CO2-Headspace Test, GLP

2-BUTOXYETHANOL
Solubility in water. mg/l 1000 - 10000
Rapidly biodegradable.

ETHYL ACETATE
Solubility in water. > 10000 mg/l
Rapidly biodegradable.

(Publication JWPCF 46(1), p63-77)

N-BUTYL ACETATE

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

OECD Guideline 301 D

HYDROCARBONS, C9, AROMATICS

Rapidly biodegradable.

Biodegradazione 78% in 28 d (OECD Guideline 301 F)

REACTION MASS OF A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-HYDROXYPOLY(OXYETHYLENE) AND A-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-Ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE).

NOT rapidly biodegradable.

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

NOT rapidly biodegradable.

12.3. Bioaccumulative potential.

2-hydroxyethyl methacrylate

Partition coefficient: n-octanol/water. 0,42 Log Kow (OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)).

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water. 3,12 American Chemical Society, Washington DC
BCF. 25,9 Appl. Sci. Branch, Eng. Res. Cent. Denver, CO: 15p.

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water. 1,2

ETHYLBENZENE

Partition coefficient: n-octanol/water. 3,6

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water. 0,81

ETHYL ACETATE

Partition coefficient: n-octanol/water. 0,68
BCF. 30

N-BUTYL ACETATE

Partition coefficient: n-octanol/water. 2,3 a 25 °C (Metodo OECD TG 117)
BCF. 15,3

12.4. Mobility in soil.

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water.

2,73 equivalent or similar to OECD Guideline 121

N-BUTYL ACETATE

Partition coefficient: soil/water.

< 3

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.**14.1. UN number.**

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name.

ADR / RID: PAINT or PAINT RELATED MATERIAL (Contens: XYLENE (MIXTURE OF ISOMERS), n-BUTHYL ACETATE, HYDROCARBONS, C9, AROMATICS, ETHYL ACETATE, ETHYLBENZENE, 2-METHOXY-1-METHYLETHYL ACETATE)

IMDG: PAINT or PAINT RELATED MATERIAL (Contens: XYLENE (MIXTURE OF ISOMERS), n-BUTHYL ACETATE, HYDROCARBONS, C9, AROMATICS, ETHYL ACETATE, ETHYLBENZENE, 2-METHOXY-1-METHYLETHYL ACETATE)

IATA: PAINT or PAINT RELATED MATERIAL (Contens: XYLENE (MIXTURE OF ISOMERS), n-BUTHYL ACETATE, HYDROCARBONS, C9, AROMATICS, ETHYL ACETATE, ETHYLBENZENE, 2-METHOXY-1-METHYLETHYL ACETATE)

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3



C5101 – MAX - TRASPARENTE ACRILICO

IATA: Class: 3 Label: 3

**14.4. Packing group.**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards.

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special Provision: -		
IMDG:	EMS: F-E, S-E,	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**Seveso category. P5b FLAMMABLE LIQUIDSRestrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.Product.

Point

3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:

(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;

(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;

(c) hazard class 4.1;

(d) hazard class 5.1.

Point

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.

Contained substance.

Point. 20 DIBUTYLTIN DILAURATE Reg. no.: 01-2119496068-27-0004

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 840,00

VOC of product : 590,00

15.2. Chemical safety assessment.

A chemical safety assessment has been performed for the following contained substances.

HYDROCARBONS, C9, AROMATICS

ETHYL ACETATE

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Flam. Liq. 3 Flammable liquid, category 3

Acute Tox. 4 Acute toxicity, category 4

Asp. Tox. 1 Aspiration hazard, category 1

C5101 – MAX - TRASPARENTE ACRILICO

STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds

- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Istituto Superiore di Sanità (ISS) – Archivio Preparati Pericolosi

Codice azienda: IT00465900728

Ragione sociale: Ilpa Adesivi Srl

Nome prodotto ISS: MAX - TRASPARENTE ACRILICO H.S.

Codice prodotto ISS: C5101

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Training for workers:

Worker training should include content, updates and duration depending on the risk profiles assigned to the business sectors they belong.

Classification according to Regulation (EC) Nr. 1272/2008

Flam. Liq. 2, H225

STOT RE 2, H373

Eye Irrit. 2, H319

Skin Irrit. 2, H315

STOT SE 3, H336

Aquatic Chronic 2, H412

Classification procedure

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method